

**SOFRAPAINT**

9 -11 Rue des Cours Neuves

77135 PONTCARRE

Tél : 01.64.77.20.25

Fax : 01.64.77.20.40

**SAFETY DATA SHEET**

Emergency phone number : Centre antipoison (Paris) 01.40.37.04.04

**1. Product**

Usage Normal

**Aérosols ALPHA AEROSPACE Toutes Teintes**

aérosols peinture pour retouche

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Composants contributing to the health hazard « Substances Dangereuses 67/548/CEE, arrêté du 10/10/1983 »

NOMS	CONC	SYMBOL	PHRASE R
ACETONE	de 20 à 25 %	F	11
TOLUENE	de 0 à 5 %	F Xn	20
XYLENE	de 5 à 10 %	Xn	20/21 38
Acétate de Methoxypropanol	de 0 à 5 %	F	11
BUTANOL	de 0 à 5 %	Xn	20
2 Butoxyéthanol	de 0 à 5 %	Xn	20
Oxyde de diméthyl	de 25 à 50 %	F+	12

**3. HAZARDS IDENTIFICATION**

12 extremely inflammable  
20/21 Harmful by inhalation and in contact with skin

**4. FIRST AID MEASURES****General advice**

In all cases of doubt, or when symptoms persist, seek medical attention..

Never give anything by mouth to an unconscious person.

**Inhalation**

Remove to fresh air, keep the patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.

If unconscious, place in the recovery position and seek medical advice.

**Skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner

**Ingestion**

Do not vomit, keep quiet, and go immediately to hospital or to a doctor.

**Eye Contact**

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media** : Alcohol-resistant foam, CO<sub>2</sub>, power**Extinguishing media which must NOT be used for safety reasons** : Do not use water jet**Specific method** :

Fire will produce dense black smoke. Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required.

Cool closed containers exposed to fire with water spray.

**6. ACCIDENTAL RELEASE MEASURES**

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillages with non-combustible absorbant materials, e.g. sand, earth, vermiculite, diatomaceous earth.

Prevent liquid from entering sewers, watercourses, underground or low areas.

---

---

## 7. HANDLING AND STORAGE

### Handling

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

Smoking, eating and drinking should be prohibited in areas of storage and use.

For personal protection, see section 8.

Refer to the guide weight indicated on the container when carrying out assessments.

### Storage

Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store at temperatures between 5°C and 40°C.

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

No smoking.

---

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Engineering measure :

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and / or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn.

### Exposure limit(s)

	VLE(1)		VME (2)	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
TOLUENE			100	375
XYLENE			100	435

### Personal protection equipment

#### Respiratory protection

In order to avoid inhalation of mist / vapour, all working must be done wearing adequate respirator.

#### Hand protection

#### Eye protection

Eye protection designed to protect against liquid splashes should be worn.

#### Skin protection

(1) VLE valeur limite d'exposition à court terme (15 min)

(2) VME valeur limite moyenne d'exposition moyenne à long terme (8h/jour)

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE : LIQUID

FLASH POINT : < à 21°C

Water solubility : partly miscible

Relative density : heavier than air

masse spécifique :

---

---

## 10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions. (see section 7). Avoid temperature above 30°C. Heating will cause rise in pressure with risk bursting.

Tout appareil susceptible de produire une flamme ou de porter à une haute température une surface métallique sera banni des locaux.

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

---

---

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

---

---

## 12. ECOLOGICAL INFORMATION

There is no data available on the product itself.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

---

---

## 13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.  
Empty containers can be dumped according to local legislation.

---

---

#### 14. TRANSPORT INFORMATION

##### LAND (Road / railway : ADR/RID)

Aérosols

N° ONU : 1950

Item and letter : 5°F

Label code : 3

Class : 2

##### Sea (IMDG)

Code : 2102

N° ONU : 1950

Class : 2

Group : II

N° litem 2-13

##### Air( ICAO/ IATA)

N° ID : 8000

Class : 9

N° ONU : 1950

---

---

#### 15. REGULATORY INFORMATION

Symbol F+ Xn

Contains : Toluène, xylène

PHRASES R 20/21 12

PHRASES S23 38 36/37

---

---

#### 16. OTHER INFORMATION

##### RISQUES

20/21 HARMFUL BY INHALATION AND IN CONTACT WITH SKIN

12 EXTREMELY INFLAMMABLE

##### SECURITE

23 DO NOT BREATHE GAS / FUMES / VAPOUR / SPRAY

36/37 WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES

38 IN CASE OF INSUFFICIENT VENTILATION WEAR SUITABLE RESPIRATORY EQUIPEMENT